

 <p>ST-1 Straight pins ST-1B Angled pins 3~25A 125/250VAC/32VDC</p>	 <p>ST-001S Short 3pin w/ LED 3~20A 125/250VAC/32VDC</p>	 <p>ST-003L Long 3pin w/ LED 3~20A 125/250VAC/32VDC</p>	 <p>KSD301A-OF2 NO Type KSD301B-OF2 NC Type 0°C~260°C 10A/16A 250VAC</p>
 <p>ST-2P 15~50A 125/250VAC/32VDC</p>	 <p>ST-001L Long 3pin w/ LED 3~20A 125/250VAC/32VDC</p>	 <p>ST-002 5~20A 125/250VAC/32VDC</p>	 <p>KSD301A-OR2 NO Type KSD301B-OR2 NC Type 0°C~260°C 10A/16A 250VAC</p>
 <p>ST-2A 15~50A 125/250VAC/32VDC</p>	 <p>ST-003S-101 Short 2pin ST-003L-101 Long 2pin 3~20A 125/250VAC/32VDC</p>	 <p>RY-01 Thermo fuse 65°C~285°C 10A/15A 250VAC</p>	 <p>KSD301M-OF2 Manual reset NC Type 75°C~185°C 10A/16A 250VAC</p>
 <p>ST-001S-101 Short 2pin ST-001L-101 Long 2pin 3~20A 125/250VAC/32VDC</p>	 <p>ST-003S Short 3pin w/ LED 3~20A 125/250VAC/32VDC</p>	 <p>TLRS-9700P (Plastic Type) 40°C~120°C 5A 250VAC TLRS-9700M (Metal Type) 40°C~150°C 5A 250VAC</p>	 <p>KSD301M-BR2 Manual reset NC Type 75°C~185°C 10A/16A 250VAC</p>