



安装面板

PANEL CUT-OUT



电路图 Circuit



主要技术参数、性能
The Main Technology Performance

项目 Item	参数 Parameter
额定电压、电压 Rated Voltage	3A 250VAC
额定电流 Rated current	
绝缘电阻 Insulated resistance	DC 500V 100M Ω min
接触电阻 Contact resistance	50m Ω Max
介电强度(辅助) Dielectric strength	AC 1500V 1 minute
操作温度 Operating Temperature	-25 $^{\circ}$ C ~ +85 $^{\circ}$ C
电寿命 Electrical life	≥ 10000 Cycles

弹簧 Spring 1 Spring steel wire 弹簧钢丝 0.6mm

接触片 Contact 1 Brass Plated silver

脚 terminal 2 Brass Plated silver

底部 Bottom 1 PMSI

身体 housing 1 PMSI

头部 Button 1 PC

名称 NAME 数量 Q'TY 材料 MATERIAL 表面处理 FINISHING

版本 标示 更改备注

产品型号: R16-504A

产品系列: Push Button Switch

图例比例: 1.6:1

更改有特标标示, 公称依照以下要求:

X=±0.5 .X=±0.30 .XX=±0.15 \angle=±0.2(单位: mm)

日期: 2014.1.11

日期: 2014.1.11

日期: 2014.1.11

日期: 2014.1.11

日期: 2014.1.11

日期: 2014.1.11



乐清市戴尔电子有限公司
YUEQING DAIRR ELECTRON CO., LTD



乐清市戴尔电子有限公司



乐清市戴尔电子有限公司

